

P-DG SERIES

Dual Gradient Filter Cartridges

The Aqua Flo DG cartridge filters are made from 100% polypropylene. The progressively loose structure from inside to outside enhance cartridge performance in reduction of dirt, dust and other particles.

The two separate gradient layers of the filter enhance the performance such that it achieves a much higher dirt-loading capacity compared to similar size sediment cartridge filters including spun and string-wound. These filters make an ideal sediment reduction choice for a wide range of residential, food service, commercial and industrial applications.

FEATURES / BENEFITS:


- No fiber release and media migration
- Designed for purity, bacteria and chemical resistance
- Two separate gradient density layers enhance cartridge performance
- Three times the dirt-holding capacity than other traditional sediment filters
- Available in two sizes: 4.5x10"; 4.5x20"
- Universal fit Fits most standard water filter housings
- Available in three micron ratings: 25/1; 50/5; 75/25

SPECIFICATIONS:

- > Filter Material Polypropylene
- ◆ Temperature Rating 39 145°F (4 -63°C)

APPLICATIONS (For water filtration only):

- Commercial/Residential Drinking Water Filtration
- RO Pre-filtration
- Cooling Tower Filtration
- Chill Water Loop Filtration
- > Food & Beverage Filtration
- Industrial Water Filtration





"An ideal sediment reduction choice for a wide range of residential, food service, commercial and industrial applications."

P-DG SERIES

Dual Gradient Filter Cartridges

SPECIFICATIONS & PERFORMANCE:

ITEM #	DESCRIPTION	DIMENSIONS	CASE QTY	SHIP WEIGHT EACH (LBS)	RATING (NOMINAL)	FLOW RATE (GPM)
36039	P-DG-25-1-10BV	4.5" x 10" (114.3 x 254 mm)	20	0.8	25/1	10 US GPM (38 LPM)
36043	P-DG-50-5-10BV	4.5" x 10" (114.3 x 254 mm)	20	0.8	50/5	10 US GPM (38 LPM)
36047	P-DG-75-25-10BV	4.5" x 10" (114.3 x 254 mm)	20	0.8	75/25	10 US GPM (38 LPM)
36041	P-DG-25-1-20BV	4.5" x 20" (114.3 x 508 mm)	10	2.0	25/1	20 US GPM (75.7 LPM)
36045	P-DG-50-5-20BV	4.5" x 20" (114.3 x 508 mm)	10	2.0	50/5	20 US GPM (75.7 LPM)
36049	P-DG-75-25-20BV	4.5" x 20" (114.3 x 508 mm)	10	2.0	75/25	20 US GPM (75.7 LPM)

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

NOTE: Initial flow pressure drop less than 5 psi at rated flow rate. Change filter when pressure drop exceeds 10 psi.



Your Local Water Specialist